

CABLE TIES



BULK CABLE TIE ORDERING INFORMATION

Our Cable Tie Part Numbers are easy to understand. This chart breaks down the Cable Tie Part Numbers.

CT 18 - 4 NAT - C - WR
Family Tensile Strength - Length Color - Pack Size - Options

Family	Tensile Strength	Length	Color	Pack Size	Options
CT	18	3 = 3 inches	NAT = Natural	Q = 25 pieces	WR = Weather Resistant Black
	18	4 = 4 inches	BLK = BLACK	L = 50 pieces	HS = Heat Stabilizer
	18	5 = 5 1/2 inches	RED = RED	C = 100 pieces	FR = Flame Retardent
	18	8 = 8 inches	WHT = WHITE	M = 1000 pieces	N12 = Nylon 12
	40	4 = 4 3/4 inches	BLU = BLUE		
	40	6 = 6 inches	YEL = YELLOW		
	40	8 = 8 inches	GRN = GREEN		
	40	11 = 11 1/2 inches	ORG = ORANGE		
	40	14 = 14 1/2 inches	PUR = PURPLE		
	50	4 = 4 3/4 inches	GRY = GREY		
	50	6 = 6 1/4 inches	GRN/NEON = NEON GREEN		
	50	8 = 8 inches	PNK/NEON = NEON PINK		
	50	11 = 11 inches	YEL/NEON = NEON YELLOW		
	50	14 = 14 1/2 inches	ORG/NEON = NEON ORANGE		
	50	17 = 17 inches	(Custom colors also available)		
	120	18 = 8 inches			
	120	11 = 11 inches			
	120	15 = 15 inches			
	175	17 = 17 3/4 inches			
	175	24 = 24 inches			
	175	30 = 30 inches			
	175	37 = 37 inches			
	175	48 = 48 inches			

NOTE: 18 lb tensile strength is 0.097" (2.46 mm) in width.
 40 lb tensile strength is 0.135" (3.43 mm) in width.
 50 lb tensile strength is 0.174" (4.42 mm) in width.
 120 lb tensile strength is special order only.
 175 lb tensile strength is special order only.

STOCK BULK CABLE TIES



Stock Bulk Cable Ties

Stock Bulk Cable Ties Come in Polybags in Quantities of 25, 50, 100 or 1,000 Pieces and are Our Most Popular.

Retail Part No.	Strength Classification	Max. Bundle Diameter
CT18-4NAT-C	Miniature	.625 in./15.875 mm
CT18-4NAT-M	Miniature	.625 in./15.875 mm
CT18-4BLK-C	Miniature	.625 in./15.875 mm
CT18-4BLK-M	Miniature	.625 in./15.875 mm
CT18-5NAT-C	Miniature	1.25 in./31.75 mm
CT18-5NAT-M	Miniature	1.25 in./31.75 mm
CT18-5BLK-C	Miniature	1.25 in./31.75 mm
CT18-5BLK-M	Miniature	1.25 in./31.75 mm
CT18-8NAT-C	Miniature	1.875 in./47.625 mm
CT18-8NAT-M	Miniature	1.875 in./47.625 mm
CT18-8BLK-C	Miniature	1.875 in./47.625 mm
CT18-8BLK-M	Miniature	1.875 in./47.625 mm
CT40-6NAT-C	Intermediate	1.00 in./25.4 mm
CT40-6NAT-M	Intermediate	1.00 in./25.4 mm
CT40-6BLK-C	Intermediate	1.00 in./25.4 mm
CT40-6BLK-M	Intermediate	1.00 in./25.4 mm
CT40-8NAT-C	Intermediate	1.875 in./47.625 mm
CT40-8NAT-M	Intermediate	1.875 in./47.625 mm
CT40-8BLK-C	Intermediate	1.875 in./47.625 mm
CT40-8BLK-M	Intermediate	1.875 in./47.625 mm

Retail Part No.	Strength Classification	Max. Bundle Diameter
CT40-11NAT-C	Intermediate	3.00 in./76.2 mm
CT40-11NAT-M	Intermediate	3.00 in./76.2 mm
CT40-11BLK-C	Intermediate	3.00 in./76.2 mm
CT40-11BLK-M	Intermediate	3.00 in./76.2 mm
CT40-14NAT-C	Intermediate	4.00 in./101.6mm
CT40-14NAT-M	Intermediate	4.00 in./101.6 mm
CT40-14BLK-C	Intermediate	4.00 in./101.6 mm
CT40-14BLK-M	Intermediate	4.00 in./101.6 mm
CT50-8NAT-C	Standard	1.875 in./47.625 mm
CT50-8NAT-M	Standard	1.875 in./47.625 mm
CT50-8BLK-C	Standard	1.875 in./47.625 mm
CT50-8BLK-M	Standard	1.875 in./47.625 mm
CT50-11NAT-C	Standard	3.00 in./76.2 mm
CT50-11NAT-M	Standard	3.00 in./76.2 mm
CT50-11BLK-C	Standard	3.00 in./76.2 mm
CT50-11BLK-M	Standard	3.00 in./76.2 mm
CT50-14NAT-C	Standard	4.00 in./101.6 mm
CT50-14NAT-M	Standard	4.00 in./101.6 mm
CT50-14BLK-C	Standard	4.00 in./101.6 mm
CT50-14BLK-M	Standard	4.00 in./101.6 mm

Strength Classification Uses
Miniature - Audio/Video and other small wire bundling
Intermediate - Medium Strength for Indoor/Enclosed Applications
Standard - Standard Duty for Indoor/Enclosed Applications, and Identification Purposes
Heavy Duty - Heavy Duty Bundling for Outdoor Applications

NOTE: 18 lb tensile strength is 0.097" (2.46 mm) in width.
 40 lb tensile strength is 0.135" (3.43 mm) in width.
 50 lb tensile strength is 0.174" (4.42 mm) in width.

For the latest information—www.gcelectronics.com
 All quantities are single; BU's are packages of 10 Unless otherwise noted.