



IN-WALL SPEAKER WIRE

Applications:

Audio/Stereo/Sound System Conductivity. Intercom Systems. Public Address Systems.

Features:

Stranded Bare Copper Conductors PVC Insulated Conductors. Shielded For Better Performance. Flame Retardant Jacket.



In-Wall Speaker Wire

Part Number	Color	Length	No. of Cond.	AWG	Conductor Material (Stranding)	Insulation Material	Insulation ID/ Nom. Thickness	Shield	Material (Nom. Thickness)	Cable O.D.
14-1214-2Q89	Gray	1000'	2	14	Stranded Bare Copper (19/0.36)	SR-PVC	2.4/0.225mm	Aluminum/Foil	PVC (0.50mm)	5.7mm
14-1216-2F89	Gray	1000'	2	16	Stranded Bare Copper (26/0.254)	SR-PVC	2.0/0.225mm	Aluminum/Foil	PVC (0.50mm)	5mm
14-1216-4F89	Gray	1000'	4	16	Stranded Bare Copper (19/0.36)	SR-PVC	2.0/0.225mm	Aluminum/Foil	PVC (0.50mm)	6mm
14-1216-4F25	Gray	25'	4	16	Stranded Bare Copper (19/0.36)	SR-PVC	2.0/0.225mm	Aluminum/Foil	PVC (0.50mm)	6mm
14-1216-4F1C	Gray	100'	4	16	Stranded Bare Copper (19/0.36)	SR-PVC	2.0/0.225mm	Aluminum/Foil	PVC (0.50mm)	6mm

Temperature Rating: 80°C Nom.= Nominal
 Voltage Rating: 300V AWM= Appliance Wiring Material
 UL Flammability Rating: VW-1

AWM 2547

COMPONENT SPEAKER WIRE

Applications:

Low capacitance cable for use in high definition speaker systems. Rope lay designed to increase the conductive surface, reduce "skin effect", and maximum flexibility. Low capacitance, resistance, and inductance of these cables transfer music signals from amplifier to speakers with high clarity and definition.



Oxygen Free Power Flex™ (10 gauge 2-Conductor)

Specifications:
 Oxygen Free Copper
 Conductor AWG: 10 gauge
 Stranding: 413/36
 Insulation Nominal Wall Thickness: .070
 Voltage: 300V
 Temperature Rating: -20°C to + 60°C
 Construction: Bare Oxygen Free Copper Conductors; Flexible PVC Insulation and Rope Lay; Surface Print for Identification & Polarity
 Nominal O.D.: .270 x .540

Component Speaker Wire 10 AWG

Part No.	Color	Length	Packaging
14-210-9H43	Clear	100 ft.	Spool
14-210-9H53	Clear	250 ft.	Spool
14-210-9H63	Clear	500 ft.	Spool
30-581	Clear	25 ft.	Hank

Oxygen Free Power Flex™ (12 gauge 2-Conductor)


Specifications:
 Oxygen Free Copper
 Conductor AWG: 12 gauge
 Stranding: 259/36
 Insulation Nominal Wall Thickness: .055
 Voltage: 300V
 Temperature Rating: -20°C to + 60°C
 Construction: Bare Oxygen Free Copper Conductors; Extra Flexible PVC Insulation and Rope Lay; Surface Print for Identification & Polarity
 Nominal O.D.: .205 x .415

Component Speaker Wire 12 AWG

Part No.	Color	Length	Packaging
14-212-9H43	Clear	100 ft.	Spool
14-212-9H53	Clear	250 ft.	Spool
14-212-9H63	Clear	500 ft.	Spool
30-583	Clear	25 ft.	Hank

COMPONENT SPEAKER WIRE (Cont.)

2 Conductor Parallel Zip Cord



Two conductor Parallel Zip Cord Wire for loudspeaker connection and other low voltage applications such as alarm, signal and telephone circuits. Temperature range:-20° to+60°. White Identification polarity stripe.

24 Gauge (2-Conductor)

Specifications:
Oxygen Free Copper
Conductor AWG: 24 gauge
Stranding: 7/32
Insulation Nominal Wall Thickness: .016"
Voltage: 300V
Temperature Rating: -20°C to + 60°C
Construction: Bare Copper Conductors; Clear PVC;
1 Conductor Identified for Polarity
Nominal O.D.: .055" x .110"

Applications:
Automotive Speaker Wire, Juke Boxes,
Stereo Speaker Wire

Part No.	Color	Length	Packaging
14-224-2B13	Clear	25 ft.	Spool
14-224-2B23	Clear	50 ft.	Spool
14-224-2B43	Clear	100 ft.	Spool
14-224-2B63	Clear	500 ft.	Spool
14-224-2B83	Clear	1000 ft.	Spool
30-586	Clear	50 ft.	Hank
30-588	Clear	100 ft.	Hank

22 Gauge (2-Conductor)

Specifications:
Oxygen Free Copper
Conductor AWG: 22 gauge
Stranding: 7/30
Insulation Nominal Wall Thickness: .020"
Voltage: 300V
Temperature Rating: -20°C to + 60°C
Construction: Bare Copper Conductors; Clear PVC;
1 Conductor Identified for Polarity
Nominal O.D.: .070" x .140"

Applications:
Automotive Speaker Wire, Juke Boxes,
Stereo Speaker Wire

Part No.	Color	Length	Packaging
14-222-2C13	Clear	25 ft.	Spool
14-222-2C23	Clear	50 ft.	Spool
14-222-2C43	Clear	100 ft.	Spool
14-222-2C63	Clear	500 ft.	Spool
14-222-2C83	Clear	1000 ft.	Spool

20 Gauge (2-Conductor)

Specifications:
Oxygen Free Copper
Conductor AWG: 20 gauge
Stranding: 7/28
Insulation Nominal Wall Thickness: .025"
Voltage: 300V
Temperature Rating: -20°C to + 60°C
Construction: Bare Copper Conductors; Clear PVC;
1 Conductor Identified for Polarity
Nominal O.D.: .085" x .170"

Applications:
Automotive Speaker Wire, Juke Boxes,
Stereo Speaker Wire

Part No.	Color	Length	Packaging
14-220-2D13	Clear	25 ft.	Spool
14-220-2D23	Clear	50 ft.	Spool
14-220-2D43	Clear	100 ft.	Spool
14-220-2D63	Clear	500 ft.	Spool
14-220-2D83	Clear	1000 ft.	Spool
30-553	Clear	50 ft.	Hank

18 Gauge (2-Conductor)

Specifications:
Oxygen Free Copper
Conductor AWG: 18 gauge
Stranding: 16/30
Insulation Nominal Wall Thickness: .025"
Voltage: 300V
Temperature Rating: -20°C to + 60°C
Construction: Bare Copper Conductors; Clear PVC;
1 Conductor Identified for Polarity
Nominal O.D.: .100" x .200"

Applications:
Automotive Speaker Wire, Juke Boxes,
Stereo Speaker Wire

Part No.	Color	Length	Packaging
14-218-2E13	Clear	25 ft.	Spool
14-218-2E23	Clear	50 ft.	Spool
14-218-2E43	Clear	100 ft.	Spool
14-218-2E53	Clear	250 ft.	Spool
14-218-2E63	Clear	500 ft.	Spool
14-218-2E83	Clear	1000 ft.	Spool
30-584	Clear	50 ft.	Hank
30-554	Clear	100 ft.	Hank

16 Gauge (2-Conductor)

Specifications:
Oxygen Free Copper
Conductor AWG: 16 gauge
Stranding: 19/29
Insulation Nominal Wall Thickness: .025"
Voltage: 300V
Temperature Rating: -20°C to + 60°C
Construction: Bare Copper Conductors; Clear PVC;
1 Conductor Identified for Polarity
Nominal O.D.: .105" x .205"

Applications:
Automotive Speaker Wire, Juke Boxes,
Stereo Speaker Wire

Part No.	Color	Length	Packaging
14-216-2F13	Clear	25 ft.	Spool
14-216-2F23	Clear	50 ft.	Spool
14-216-2F43	Clear	100 ft.	Spool
14-216-2F53	Clear	250 ft.	Spool
14-216-2F63	Clear	500 ft.	Spool
14-216-2F83	Clear	1000 ft.	Spool

14 Gauge (2-Conductor)

Specifications:
Oxygen Free Copper
Conductor AWG: 14 gauge
Stranding: 19/27
Insulation Nominal Wall Thickness: .025"
Voltage: 300V
Temperature Rating: -20°C to + 60°C
Construction: Bare Copper Conductors; Clear PVC;
1 Conductor Identified for Polarity
Nominal O.D.: .120" x .240"

Applications:
Automotive Speaker Wire, Juke Boxes,
Stereo Speaker Wire

Part No.	Color	Length	Packaging
14-214-2Q23	Clear	50 ft.	Spool
14-214-2Q43	Clear	100 ft.	Spool
14-214-2Q63	Clear	500 ft.	Spool