

## WIRE CONNECTORS and BUSHINGS



Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 12



Fig. 14



Fig. 15

### Wire Connectors

PART NO.	POLYBAG Quantity	Figure No.	Description	Gauge	Color	Type
<del>WC-1071-25P</del>	<del>25</del>	<del>1</del>	<del>Max: 1 #14 with 1 #20 Min: 2 #22</del>	<del>22-14 AWG</del>	<del>Gray</del>	<del>Screw-on</del>
WC-1072-25P	25	1	Max: 3 #16 Min: 2 #22	22-14 AWG	Blue	Screw-on
WC-1073-25P	25	1	Max: 4 #16 with 1 #18 Min: 1 #18 with 1 #20	22-14 AWG	Orange	Screw-on
WC-1074-15P	15	1	Max: 1 #10 with 2 #14 with 1 #16 Min: 3 #20	22-10 AWG	Yellow	Screw-on
WH-0006-15P	15	2	Max: 3 #10 Min: 3 #18	22-8 AWG	Red	H-type
WW-1451-15P	15	3	Max: 3 #12 Min: 2 #18	18-10 AWG	Yellow	Winged
WW-1418-8P	8	3	Max: 3 #10 Min: 3 #14 with 1 #18	18-8 AWG	Gray	Winged
WW-1454-4P	4	3	Max: 1 #8 with 3 #10 Min: 2 #10 with 1 #12	14-6 AWG	Blue	Winged
PI-1002-25P	25	4	2 Wire Connector	22-12 AWG	Red	Push-in

### Bushings

PART NO.	POLYBAG Quantity	Figure No.	Description	Mount Hole Size (mm)	Thickness (mm)	Color
SR-2614-5P	5	12	Nylon Strain Relief Bushing, Round SJT 3C, 18 AWG	15.9	3.2	Black
SR-2634-5P	5	12	Nylon Strain Relief Bushing, Round SJT 3C, 16 AWG	15.9	1.6	Black
SR-2644-5P	5	12	Nylon Strain Relief Bushing, Round SJT 3C, 16 AWG	15.9	3.2	Black
SR-2712-5P	5	12	Nylon Strain Relief Bushing, Round SJT 3C, 14 AWG	19-19.8	3.2	Black
SR-2802-5P	5	12	Nylon Strain Relief Bushing, Round SJT 3C, 12 AWG	22.2	3.2	Black
SB-3123-25P	25	14	Nylon Snap-in Bushing	8		Black
SB-3754-25P	25	14	Nylon Snap-in Bushing	9.5		Black
SB-0811-25P	25	14	Nylon Snap-in Bushing	11.1		Black
CB-0813-25P	25	15	Nylon Open/Closed Bushing	12.5-13		Black
CB-1216-20P	20	15	Nylon Open/Closed Bushing	15.5-16		Black
CB-1419-20P	20	15	Nylon Open/Closed Bushing	18-19		Black