



3100 N.W. 36th Street
Miami, FL, 33142
PH: (833) 423-0432
www.gcelectronics.com

SDS Number: 122
Revision Date: 03/24/2020
Supersedes Date: 05/12/2017

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: ACRYLIC CEMENT

SECTION 1. PRODUCT AND COMPANY INFORMATION

Product Type: Adhesive Solvent

Product Name: ACRYLIC CEMENT

Part Number(s): 10-4002

**"FOR INDUSTRIAL USE ONLY, NOT FOR HOME, SCHOOL
OR RECREATIONAL USE"**

Emergency Contact: Chemtrec

Phone: (800) 424-9300

SECTION 2. HAZARDS IDENTIFICATION

GHS CLASSIFICATION:

<u>Health</u>	<u>Environmental</u>	<u>Physical</u>
Acute Toxicity: Category 3 Skin Irritation: Category 3 Eye Irritation: Category 2 Carcinogenicity: Category 2	Acute Toxicity: None Known Chronic Toxicity: None Known	Flammable Liquid Category 2

GHS LABEL:



Signal Word:
Warning

Hazard Statements

H225: Highly flammable liquid and vapor
H319: Causes serious eye irritation
H315 + 317: Causes skin irritation. May cause an allergic skin reaction
H335: May cause respiratory irritation
H336: May cause drowsiness or dizziness
H351: Suspected of causing cancer
EUH066: Repeated exposure may cause skin dryness or cracking

Precautionary Statements

P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking
P233: Keep container tightly closed
P261: Avoid breathing dust/fume/gas/mist/vapors/spray
P280: Wear protective gloves/protective clothing/eye protection/face protection
P337+P313: If eye irritation persists: Get medical advice/attention
P403: Store in a well ventilated place.
P501: Dispose of contents/container in accordance with local regulation

Response

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/Medical Attention
P331: Do NOT induce vomiting.
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313: IF exposed or concerned: Get medical advice/attention.

Restrictions on Use (United States): Methylene chloride: This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.



3100 N.W. 36th Street
Miami, FL, 33142
PH: (833) 423-0432
www.gcelectronics.com

SDS Number: 122
Revision Date: 03/24/2020
Supersedes Date: 05/12/2017

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: ACRYLIC CEMENT

SECTION 3. COMPOSITION / INFORMATION OF INGREDIENTS

	CAS	EINECS	REACH Registration Number	CONCENTRATION % by Weight
Methylene Chloride*# (Dichloromethane)	75-09-2	200-838-9	01-2119480404-41-0000	30 - 60
Methyl Acetate	79-20-9	201-185-2	01-2119459211-47-0000	10 - 15
Methyl Ethyl Ketone (MEK)	78-93-3	201-159-0	01-2119457290-43-0000	10 - 30
Methyl Methacrylate Monomer*, Stabilized (MMA)	80-62-6	201-297-1	01-2119452498-28-0000	0 - 2

All of the constituents of this adhesive product are listed on the TSCA inventory of chemical substances maintained by the US EPA, or are exempt from that listing. * Indicates this chemical is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 (40CFR372). # indicates that this chemical is found on Proposition 65's List of chemicals known to the State of California to cause cancer or reproductive toxicity.

SECTION 4. FIRST AID MEASURES

Contact with eyes: Flush eyes immediately with plenty of water for 15 minutes and seek medical advice immediately.
Skin contact: Wash skin with soap and water. If irritation develops, get medical attention
Inhalation: Remove to fresh air. If breathing is stopped, give artificial respiration. If breathing is difficult, give oxygen. Seek medical advice.
Ingestion: Do not induce vomiting. Seek medical advice immediately.

SECTION 5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Water fog or fine spray, carbon dioxide, dry chemical or foam.
Unsuitable Extinguishing Media: Dry chemical powder.
Exposure Hazards: Inhalation and dermal contact.
Combustion Products: Hydrogen chloride, trace amounts of chlorine, phosgene.
Protection for Firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing.

	HMIS	NFPA	
Health	2	2	1-Minimal
Flammability	3	3	2-Slight
Reactivity	1	1	3-Moderate
			4-Serious
			5-Severe

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Clear all personnel from area. Do not breathe vapors. Ventilate area of leak or spill. Wear protective equipment positive pressure self contained or air supplied breathing apparatus. Follow confined space entry procedures.
Environmental Precautions: Prevent product or liquids contaminated with product from entering sewers, drains, soil or open water course.
Methods for Cleaning up: Mop or soak up immediately. Place in properly labeled metal containers.
Materials Not to be used for clean up: Zinc, Aluminum or plastic containers

SECTION 7. HANDLING AND STORAGE

Handling: Avoid breathing of vapor, avoid contact with eyes, skin and clothing. Do not swallow. Use with adequate ventilation. Do not cut, drill, grind, weld or perform similar operations on or near empty containers. Vapors of this product are heavier than air and will collect in low areas. Do not eat, drink or smoke while handling.
Storage: Store in a dry place. Keep container tightly closed when not in use. Store below 80°F (27°C). Follow all precautionary information on container label, product bulletins and solvent bonding literature.



3100 N.W. 36th Street
Miami, FL, 33142
PH: (833) 423-0432
www.gcelectronics.com

SDS Number: 122
Revision Date: 03/24/2020
Supersedes Date: 05/12/2017

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: ACRYLIC CEMENT

SECTION 8. PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS:	Component	ACGIH 8 hr-TLV	ACGIH 15 min-STEL	OSHA 8 hr-PEL	OSHA 15 Min-STEL	OSHA PEL-Ceiling	CAL/OSHA 8 Hr-PEL	CAL/OSHA Ceiling	CAL/OSHA 15 Min-STEL
	Methylene Chloride	50 ppm	N/E	25 ppm	125 ppm	N/E	N/E	N/E	N/E
	Methyl Acetate	200 ppm	250 ppm	200 ppm	250 ppm	N/E	200 ppm	N/E	250 ppm
	Methyl Ethyl Ketone (MEK)	200 ppm	300 ppm	200 ppm	300 ppm	N/E	200 ppm	N/E	300 ppm
	Methyl Methacrylate Monomer	50 ppm	100 ppm	100 ppm	N/E	N/E	50 ppm	100 ppm	N/E

Engineering Controls: Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines. Lethal concentrations may exist in areas with poor ventilation.

Monitoring: Maintain breathing zone airborne concentrations below exposure limits.

Personal Protective Equipment (PPE):

Eye Protection: Use chemical goggles. If exposure causes eye discomfort, use a full-face respirator.

Skin Protection: Prevent contact with the skin as much as possible. Use protective clothing chemically resistant to this material. Remove contaminated clothing immediately, wash skin area with soap and water and launder clothing before reuse or dispose of properly.

Respiratory Protection: Prevent inhalation of the solvents. Use in a well-ventilated room. Open doors and/or windows to ensure airflow and air changes. Use local exhaust ventilation to remove airborne contaminants from employee breathing zone and to keep contaminants below levels listed above. With normal use, the Exposure Limit Value will not usually be reached. When limits approached, use respiratory protection equipment.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear, medium syrupy liquid

Odor: Ketone

pH: Not Applicable

Melting/Freezing Point: -99°C (-146°F) (Methyl Acetate)

Boiling Point: 39.8°C (104°F) Based on first boiling component: Methylene Chloride

Flash Point: -10°C (14°F) (Methyl Acetate)

Specific Gravity: 1.107 @23°C (73.4°F)

Solubility: 32g/100g H₂O (Methyl Acetate)

Partition Coefficient n-octanol/water: Not Available

Auto-ignition Temperature: 454°C (849°F) (Methyl Acetate)

Decomposition Temperature: Not Applicable

VOC Content: When applied as directed, per SCAQMD Rule 1168, Test Method 316A, VOC content is: <250 g/l.

Odor Threshold: 5.4 ppm (MEK)

Evaporation Rate: > 1.0 (BUAC = 1)

Flammability: None

Flammability Limits: LEL: 1.4% (MEK) UEL: 22% (Methylene Chloride)

Vapor Pressure: 355 mmHG @ 20°C (Methylene Chloride)

Vapor Density: >2.0 (Air = 1)

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Heating may cause a fire.

Stability: Stable under recommended storage conditions. (See Section 7)

Hazardous decomposition products: Depending on temperature and air supply, may include hydrogen chloride, trace amounts of chlorine, phosgene.

Conditions to avoid: Avoid open flames, welding arcs, or other high temperature sources. Avoid direct sunlight.

Incompatible Materials: Oxidizers, strong bases, amines, metals such as zinc powders, aluminum or magnesium powders, potassium sodium.

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: ACRYLIC CEMENT

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Inhalation, Eye and Skin Contact

Acute symptoms and effects:

Inhalation: Excessive overexposure may cause irritation to nose and throat. In confined areas, vapor can accumulate and can cause unconsciousness.

Eye Contact: May cause moderate eye irritation which may be slow to heal. May cause slight corneal injury. Vapor may cause mild discomfort and redness.

Skin Contact: Prolonged contact may cause skin burns. May cause more severe response on covered skin (under clothing and gloves).

Ingestion: Low toxicity if small amount swallowed, however larger amounts may cause injury. Aspiration into the lungs may occur during ingestion or vomiting.

Chronic (long-term) effects: IARC Classification 2B (Methylene Chloride)

Toxicity:	LD ₅₀	LC ₅₀	Target Organs
Methylene Chloride (dichloromethane)	Oral: 1500- 2500 mg/kg (rat) , Dermal: Not Determined	Inhalation 7 hrs. >10000 PPM (rat)	STOT SE3
Methyl Acetate	Oral: > 5000 mg/kg (oral/rabbit)	Inhalation 4 hrs. 12000 PPM (rat)	STOT SE3
Methyl Ethyl Ketone (MEK)	Oral: 2737 mg/kg (rat), Dermal: 6480 mg/kg (rabbit)	Inhalation 8 hrs. 23,500 mg/m ³ (rat)	STOT SE3
Methyl Methacrylate Monomer, Stabilized (MMA)	Oral: 7900 mg/kg (rat), Dermal: >35000 mg/kg (rabbit)	Inhalation: 3 hrs. 7093 PPM (rat)	STOT SE3

<u>Reproductive Effects</u>	<u>Teratogenicity</u>	<u>Mutagenicity</u>	<u>Embryotoxicity</u>	<u>Sensitization to Product</u>	<u>Synergistic Products</u>
Not Established	Not Established	Not Established	Not Established	Not Established	Not Established

Acute Toxicity

Methyl Ethyl Ketone (MEK)	Acute (Oral) Toxicity: None	Acute (Dermal) Toxicity: None	Acute (Inhalation) Toxicity: None
Methylene Chloride	Acute (Oral) Toxicity: Nausea, vomiting, risk of aspiration upon vomiting., Aspiration may cause pulmonary oedema & pneumonitis.		
	Acute (Dermal) Toxicity: None		
	Acute (Inhalation) Toxicity: Possible damages:, mucosal irritations		

Specific Target Exposure Toxicity (Single Exposure): Category 3

Specific Target Exposure Toxicity (Repeated Exposure): Not Applicable

<u>Reproductive Effects</u>	<u>Teratogenicity</u>	<u>Mutagenicity</u>	<u>Embryotoxicity</u>	<u>Sensitization to Product</u>	<u>Synergistic Products</u>
Methylene Chloride-Prop 65	Not Established	Not Established	Not Established	Not Established	Not Established

Carcinogenicity: Methylene Chloride - IARC Classification 2B
Methylene Chloride (CAS# 75-09-2) is on the Proposition 65's List of chemicals known to the State of California to cause cancer or reproductive toxicity.

Aspiration Hazard: Based on available data, the classification criteria are not met.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity:	LC ₅₀	LC ₅₀	EC ₅₀
Acute Aquatic Toxicity	Pimephales promelas (fathead minnow); 96-hour	Daphnia magna (water flea): 48-hour	Pseudokirchneriella subcapitata (microalgae) Growth rate inhibitor
Methyl Ethyl Ketone	> 100 mg/L	> 100 mg/L	2,029 mg/l - 96 hour

Mobility in Soil: If released into the environment, this product can move rapidly through the soil.

Degradability: Does not degrade rapidly based on quantitative tests. (Tetrahydrofuran)

Bioaccumulation: This product and its degradation products are not known to bioaccumulate..

Results of PBT and vPvB assessment: PBT: Not applicable. vPvB: Not applicable

Other adverse effects: No relevant information available.

SECTION 13. WASTE DISPOSAL CONSIDERATIONS

Dispose of waste and containers in compliance with applicable Federal, State, Provincial, and Local regulations.
Consult disposal expert.



3100 N.W. 36th Street
Miami, FL, 33142
PH: (833) 423-0432
www.gcelectronics.com

SDS Number: 122
Revision Date: 03/24/2020
Supersedes Date: 05/12/2017

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: ACRYLIC CEMENT

SECTION 14. TRANSPORT INFORMATION

Proper Shipping Name:	Adhesives	Identification Number:	UN 1133
Hazard Class:	3	Packing Group:	PG II
Secondary Risk:	None	Label Required:	Class 3 Flammable Liquid
		Marine Pollutant:	NO

EXCEPTION for Ground Shipping

DOT Limited Quantity: Up to 5L per inner packaging, 30 kg gross weight per package.

Consumer Commodity: Depending on packaging, these quantities may qualify under DOT as ORM-D

TDG INFORMATION

TDG CLASS:	FLAMMABLE LIQUID 3
SHIPPING NAME:	ADHESIVES
UN NUMBER/PACKING GROUP:	UN 1133, PG II

SECTION 15. REGULATORY INFORMATION

Precautionary Label Information: Flammable, Harmful, Suspected Carcinogen Ingredient Listings: USA TSCA, Europe EINECS, Canada DSL, Australia,

Symbols: F, Xn AICS, Korea ECL/TCCL, Japan MITI (ENCS), **CA Prop 65**

Compliance Statement: This SDS was prepared to be in accordance with:

US OSHA Hazard Communication Standard 29 CFR 1910.1200 (Rev 2012)

Canadian Workplace Hazardous Materials Information System (WHMIS) 2015

European Regulation (EC) No (EU) 2015/830 on classification, labelling and packaging of substances and mixtures

Toxic Substance Control Act (TSCA) Restriction of Use: Methylene chloride

This chemical /product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

OSHA SPECIFICALLY REGULATED SUBSTANCES:

OSHA 29 CFR 1910.1052 (Methylene chloride); The U.S. Department of Labor, Occupational Safety and Health Administration specifically regulates manufacturing, handling and processing of Methylene chloride. Such regulations have been published at 29 CFR 1910.1052

Written notification is required to the EPA once annually when this product is exported to a new country.

SECTION 16. OTHER INFORMATION

All ingredients are compliant with the requirements of the European Directive on RoHS (Restriction of Hazardous Substances).

This product is intended for use by skilled individuals at their own risk. The information contained herein is based on data considered accurate based on current state of knowledge and experience. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof.

Training necessary: Yes, training in practices and procedures contained in product literature.

GC Electronics believes that the information contained herein is accurate and reliable as of the date of this material safety data sheet, but no representation guarantee or warranty, express or implied, is made as to the accuracy, reliability or completeness of the information. Persons receiving information are encouraged to make their own determination as to the information's suitability and completeness for their particular application.

NO INFORMATION CONTAINED HEREIN CONSTITUTES A PRODUCT WARRANTY OF ANY KIND, WHETHER EXPRESS OR IMPLIED; AND ALL IMPLIED WARRANTIES OF MERCHANT ABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED BY GC ELECTRONICS.