



3100 N.W. 36th Street
Miami, FL, 33142
(833) 423-0432
www.gcelectronics.com

SDS Number: 333
Revision Date: 10/26/2021
Supersedes Date: New

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: GC FREEZE MIST

SECTION 1- PRODUCT AND COMPANY IDENTIFICATION

Product Type: Freeze Mist
Product Name: **GC FREEZE MIST**
Part Number(s): 19-8410-HFO

Emergency Contact: **Chemtrec**
Phone: **(800) 424-9300**

COMMON NAME (used on label)(Trade Name & Synonyms): **GC FREEZE MIST**

Synonyms: trans-1,3,3,3-Tetrafluoroprop-1-ene
Use of the substance/mixture: Follow Label Directions
Use of the substance/mixture: Electronic component freeze spray

SECTION 2- HAZARDS IDENTIFICATION

Classification of the substance or mixture

Gases Under Pressure -Liquefied Gas, H280

GHS label elements

Warning



Contains gas under pressure; may explode if heated

Protect from sunlight. Store in a well-ventilated place.

Other hazards which do not result in classification

Rapid evaporation of the liquid may cause frostbite. Vapors are heavier than air and can cause suffocation by reducing available oxygen. May cause cardiac arrhythmia. Misuse or intentional inhalation can be fatal as a result of effects on the heart, without alarming symptoms.

Note: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The actual container label will not include the label elements above. The labeling above applies to industrial/professional products.



3100 N.W. 36th Street
Miami, FL, 33142
(833) 423-0432
www.gcelectronics.com

SDS Number: 333
Revision Date: 10/26/2021
Supersedes Date: New

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: GC FREEZE MIST

SECTION 3- COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	%
trans-1,3,3,3-Tetrafluoroprop-1-ene (Active ingredient)	29118-24-9	100

SECTION 4- FIRST AID MEASURES

Description of necessary first-aid measures

Eye Contact:	For liquid contact, irrigate with running water for minimum of 15 minutes. Seek medical attention.
Skin Contact:	For liquid contact, warm areas gradually and get medical attention if there is evidence of frost bite or tissue damage. Flush area with lukewarm water. Do not rub affected area. If blistering occurs, apply a sterile dressing. Seek medical attention.
Inhalation:	Remove to fresh air. Artificial respiration and/or oxygen may be necessary. Consult a physician.
Ingestion:	This material is a gas under normal atmospheric conditions and ingestion is unlikely.

Most important symptoms/effects, acute and delayed

Acute:	Anesthetic effects at high concentrations.
Delayed:	None known or anticipated. See Section 11 for information on effects from chronic exposure, if any.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician: Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to high concentrations (e.g., in enclosed spaces or with deliberate abuse). The use of other drugs with less arrhythmogenic potential should be considered. If sympathomimetic drugs are administered, observe for the development of cardiac arrhythmias.



3100 N.W. 36th Street
Miami, FL, 33142
(833) 423-0432
www.gcelectronics.com

SDS Number: 333
Revision Date: 10/26/2021
Supersedes Date: New

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: GC FREEZE MIST

SECTION 5- FIRE FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water Mist, Dry Powder, Foam, Carbon Dioxide.

Specific hazards arising from the chemical

Unusual Fire and Explosion Hazards: If container is not properly cooled, it can rupture in the heat of a fire. Drains can be plugged and valves made inoperable by the formation of ice if rapid evaporation of large quantities of the liquefied gas occurs.

Hazardous Combustion Products: Hazardous decomposition products may include: Hydrogen Fluoride, Carbonyl fluoride. Carbon Oxides.

Special protective actions for fire-fighters

Self-contained breathing apparatus (SCBA) is required if containers rupture and contents are released under fire conditions. Cool containers/ tanks with water spray. Product is not combustible under normal conditions. However, this material can ignite when mixed with air under pressure and exposed to strong ignition sources. Do not allow run-off from fire fighting to enter drains or water courses. Vapors are heavier than air and can cause suffocation by reducing oxygen available for breathing. Some risk may be expected of corrosive and toxic decomposition products. Fire may cause evolution of: Hydrogen fluoride

SECTION 6- ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus. Keep upwind of leak -evacuate until gas has dispersed.

Environmental precautions

Stop spill/release if it can be done safely. Water spray may be useful in minimizing or dispersing vapors. If spill occurs on water notify appropriate authorities and advise shipping of any hazard.

Methods and materials for containment and cleaning up

Ventilate area using forced ventilation, especially low or enclosed places where heavy vapors might collect. Notify relevant authorities in accordance with all applicable regulations.



3100 N.W. 36th Street
Miami, FL, 33142
(833) 423-0432
www.gcelectronics.com

SDS Number: 333
Revision Date: 10/26/2021
Supersedes Date: New

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: GC FREEZE MIST

SECTION 6- ACCIDENTAL RELEASE MEASURES (CONTINUED)

Recommended measures are based on the most likely spillage scenarios for this material; however local conditions and regulations may influence or limit the choice of appropriate actions to be taken.

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with cleanup. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

SECTION 7- HANDLING AND STORAGE

Precautions for safe handling

Comply with state and local regulations. Avoid contact with skin, eyes and clothing. Avoid breathing vapors. Wash hands thoroughly after handling. Wash clothing after use. Decomposition will occur when product comes in contact with open flame or electrical heating elements. Use good personal hygiene practices and wear appropriate personal protective equipment (see section 8).

Contents are under pressure. Gases can accumulate in confined spaces and limit oxygen available for breathing. Use only with adequate ventilation. Do not enter confined spaces such as tanks or pits without following proper entry procedures such as ASTM D-4276 and 29CFR 1910.146.

Conditions for safe storage, including any incompatibilities

Keep container(s) tightly closed and properly labeled. Use and store this material in cool, dry, well ventilated areas away from heat, direct sunlight. Store only in approved containers. Protect container(s) against physical damage. "Empty" containers retain residue and may be dangerous.

SECTION 8- EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Component	ACIGH TLV (TWA)	ACIGH TLV (STEL)	OSHA PEL (TWA)	OTHER PEL
trans-1,3,3,3-Tetrafluoroprop-1-ene				800 ppm Honeywell AEL

Appropriate engineering controls

Use only with adequate ventilation. Keep container tightly closed.

Individual protection measures

Eye/Face Protection:

The use of eye protection (such as splash goggles) that meets or exceeds ANSI Z.87.1 is recommended when there is potential liquid contact to the eye. Depending on conditions of use, a face shield may be necessary.



3100 N.W. 36th Street
Miami, FL, 33142
(833) 423-0432
www.gcelectronics.com

SDS Number: 333
Revision Date: 10/26/2021
Supersedes Date: New

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: GC FREEZE MIST

SECTION 8- EXPOSURE CONTROLS / PERSONAL PROTECTION (CONTINUED)

Skin Protection: Impervious, insulated gloves recommended.

Respiratory Protection: Wear NIOSH approved respiratory protection as appropriate.

Suggestions provided in this section for exposure control and specific types of protective equipment are based on readily available information. Users should consult with the specific manufacturer to confirm the performance of their protective equipment. Specific situations may require consultation with industrial hygiene, safety, or engineering professionals.

SECTION 9- PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Appearance & Odor:	Clear, colorless liquefied gas with a slight ethereal odor.
Odor Threshold:	No Data
pH:	Not Applicable
Melting/ Freezing Point:	No Data
Flash Point (Method) :	None per ASTM E681
Lower Explosion Limit:	None < 28°C
Vapor Pressure @ 70 °F:	49 PSIG
Specific Gravity (H2O = 1.00):	1.19
Percent Volatile by Volume:	100%
Initial Boiling Point/ Range:	-19 °C
Evaporation Rate:	> 1 (Ethyl Ether= 1.0)
Upper Explosion Limit:	None < 28°C
Vapor Density (air= 1.00):	3.9
Solubility in Water @ 70 °F:	0.0373%
Auto-ignition temperature:	368 °C
Decomposition Data:	No Data
Viscosity:	No Data



3100 N.W. 36th Street
Miami, FL, 33142
(833) 423-0432
www.gcelectronics.com

SDS Number: 333
Revision Date: 10/26/2021
Supersedes Date: New

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: GC FREEZE MIST

SECTION 10- STABILITY AND REACTIVITY DATA

Chemical stability

Stable at normal temperatures and conditions

Possibility of hazardous reactions

Does not occur

Conditions to avoid

When pressurized with air or oxygen, the mixture may become flammable. Certain mixtures of HCFCs or HFCs with chlorine may become flammable or reactive under certain conditions. To avoid thermal decomposition, do not overheat.

Incompatible materials

Alkali or Alkaline Earth Metals. Powdered Metal. Powdered Metal Salts.

Hazardous decomposition products

Carbon oxides, Hydrogen fluoride, Carbonyl fluoride, Fluorocarbons.

SECTION 11- TOXICOLOGICAL INFORMATION

Toxicological (health) effects

Effects of Over Exposure

Ingestion:	Aspiration hazard!
Inhalation:	Inhalation of vapor may produce anesthetic effects and feeling of euphoria. Prolonged overexposure can cause rapid breathing, headache, dizziness, narcosis, unconsciousness, and death from asphyxiation, depending on concentration and time of exposure.
Skin Contact:	Contact with evaporating liquid can cause frostbite.
Eye Contact:	Liquid can cause severe irritation, redness, tearing, blurred vision, and possible freeze burns.
Specific Target Organ Toxicity (Single Exposure):	Not expected to cause organ effects from single exposure.
Specific Target Organ Toxicity (Repeated Exposure):	Not expected to cause organ effects from repeated exposure.
Carcinogenicity:	Not expected to cause cancer. This substance is not listed as a carcinogen by IARC, NTP or OSHA.
Germ Cell Mutagenicity:	Not expected to cause heritable genetic effects.
Reproductive Toxicity:	Not expected to cause reproductive toxicity.
Other Comments:	High concentrations may reduce the amount of oxygen available for breathing, especially in confined spaces. Hypoxia (inadequate oxygen) during pregnancy may have adverse effects on the developing fetus.

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: GC FREEZE MIST

SECTION 11- TOXICOLOGICAL INFORMATION (CONTINUED)

Information on Toxicological Effects of Components

trans-1,3,3,3-Tetrafluoropro-1-ene

Acute inhalation toxicity:

Species: mouse

Note: Acute (4-Hour) Inhalation Toxicity Screening Study
(mouse): No lethality at >100,000 ppm.

LC50: > 207000 ppm

Exposure time: 4 h

Species: rat

Skin irritation:

Species: rabbit

Result: No skin irritation

Method: OECD Test Guideline 404

Sensitisation:

Cardiac sensitization

Species: dogs

Result: Did not cause sensitisation on laboratory animals.

Repeated dose toxicity:

Species: rat

Application Route: Inhalation

Exposure time: 13 Weeks

Note: Causes mild effects on the heart. NOEL 5,000 ppm

Genotoxicity in vitro:

Test Method: Chromosome aberration test in vitro

Cell type: Human lymphocytes

Result: negative Test Method: Ames test Result: negative

Genotoxicity in vivo:

Test Method: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)

Species: mouse

Cell type: Micronucleus

Application Route: Inhalation

Result: negative

Teratogenicity:

Species: rabbit

Method: Prenatal Developmental Inhalation Toxicity Study

Note: Did not show teratogenic effects in animal experiments.

Species: rat

Method: Prenatal Developmental Inhalation Toxicity Study

Note: Did not show teratogenic effects in animal experiments.

Further information:

Note: Excessive exposure may cause central nervous system effects including drowsiness and dizziness. Excessive exposure may also cause cardiac arrhythmia. Rapid evaporation of the liquid may cause frostbite.

Product Name: GC FREEZE MIST**SECTION 12- ECOLOGICAL INFORMATION****Toxicity**Ecotoxicity effects

Toxicity to fish: NOEC: > 117 mg/l Exposure time: 96 h Species: Cyprinus carpio (Carp)
Toxicity to daphnia and other aquatic invertebrates: ECS0: > 160 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea)
Toxicity to algae: Growth inhibition NOEC: > 170 mg/l Exposure time: 72 h Species: Algae

Persistence and degradability

Aerobic Result: Not readily biodegradable. Further information on ecology
Additional ecological Information: no data available

Bioaccumulative potential

Not expected as having the potential to bioaccumulate.

Mobility in soil Due to the extreme volatility of liquefied gases, air is the only environmental compartment in which they will be found.

Other adverse effects None anticipated trans-1,3,3,3-Tetrafluoropropane: GWP 6

SECTION 13- DISPOSAL CONSIDERATIONS**Disposal methods**

Waste Disposal Reclaim by distillation, incinerate, or remove to a permitted waste facility.

Environmental Hazards Empty pressure vessels should be returned to the supplier.

**Comply With All State and Local Regulations **

SECTION 14- TRANSPORT INFORMATION

UN Number UN3163
UN Proper Shipping Name Liquefied Gas, N.O.S., 2.2
(trans-1,3,3,3-Tetrafluoropropane)
Transport hazard class(es) 2.2

SECTION 15- REGULATORY INFORMATION**Safety, health and environmental regulations specific for the product in question**Regulatory Information

Chemical Inventories USA TSCA: All components of this product are listed on the TSCA Inventory.
SARA Title III:

CERCLA/SARA (Section 302) Extremely Hazardous Substances and TPQs (in pounds):

This material does not contain any chemicals subject to the reporting requirements of SARA 302 and 40 CFR 372.

SARA (311, 312) Hazard Class: Acute Health: Yes Chronic Health: No
Fire Hazard: No Pressure Hazard: Yes

SARA (313) Chemicals: Not listed

California Proposition 65: This material does not contain any chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm at concentrations that trigger the warning requirements of California Proposition 65.

SECTION 16- OTHER INFORMATION

GC Electronics believes that the information contained herein is accurate and reliable as of the date of this material safety data sheet, but no representation guarantee or warranty, express or implied, is made as to the accuracy, reliability or completeness of the information. Persons receiving information are encouraged to make their own determination as to the information's suitability and completeness for their particular application. NO INFORMATION CONTAINED HEREIN CONSTITUTES A PRODUCT WARRANTY OF ANY KIND, WHETHER EXPRESS OR IMPLIED; AND ALL IMPLIED WARRANTIES OF MERCHANT ABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED BY GC ELECTRONICS.