

## HOOK-UP and LEAD SPEAKER WIRE

### 26 AWG

**Specifications:**

Stranding: 7/34  
 Insulation Thickness: .010" (Stranded), .009" (Solid)  
 Insulation Material: Semi-rigid PVC  
 Nominal O.D.: .039" (Stranded), .036" (Solid)  
 Maximum Rating: 300 Volts  
 Amps Rating: 4 Amps  
 Packaging: Spool



**Stranded (Tinned Copper)**

25 Feet	100 Feet	1000 Feet	Color
14-426-1H10	<del>14-426-1H40</del>	<del>14-426-1H80</del>	Gray
14-426-1H11	14-426-1H41	14-426-1H81	Black
14-426-1H12	14-426-1H42	14-426-1H82	Brown
14-426-1H13	14-426-1H43	14-426-1H83	Orange
14-426-1H14	14-426-1H44	14-426-1H84	Off-White
14-426-1H15	14-426-1H45	<del>14-426-1H85</del>	Violet
14-426-1H16	14-426-1H46	14-426-1H86	Red
14-426-1H17	14-426-1H47	<del>14-426-1H87</del>	Green
14-426-1H18	14-426-1H48	<del>14-426-1H88</del>	Yellow
14-426-1H19	14-426-1H49	<del>14-426-1H89</del>	Light Blue

**Solid (Tinned Copper)**

25 Feet	100 Feet	1000 Feet	Color
14-426-1K10	14-426-1K40	14-426-1K80	Gray
14-426-1K11	14-426-1K41	14-426-1K81	Black
14-426-1K12	14-426-1K42	14-426-1K82	Brown
14-426-1K13	14-426-1K43	14-426-1K83	Orange
14-426-1K14	14-426-1K44	14-426-1K84	Off-White
14-426-1K15	14-426-1K45	14-426-1K85	Violet
<del>14-426-1K16</del>	14-426-1K46	14-426-1K86	Red
14-426-1K17	14-426-1K47	<del>14-426-1K87</del>	Green
14-426-1K18	14-426-1K48	14-426-1K88	Yellow
14-426-1K19	14-426-1K49	<del>14-426-1K89</del>	Light Blue

### 24 AWG

**Specifications:**

Stranding: 7/32  
 Insulation Thickness: .010"  
 Insulation Material: Semi-rigid PVC  
 Nominal O.D.: .044" (Stranded), .040" (Solid)  
 Maximum Rating: 300 Volts  
 Amps Rating: 6 Amps  
 Packaging: Spool



**Stranded (Tinned Copper)**

25 Feet	100 Feet	1000 Feet	Color
14-424-1B10	14-424-1B40	14-424-1B80	Gray
<del>14-424-1B11</del>	14-424-1B41	<del>14-424-1B81</del>	Black
14-424-1B12	14-424-1B42	<del>14-424-1B82</del>	Brown
14-424-1B13	14-424-1B43	14-424-1B83	Orange
14-424-1B14	14-424-1B44	14-424-1B84	Off-White
14-424-1B15	14-424-1B45	14-424-1B85	Violet
14-424-1B16	14-424-1B46	<del>14-424-1B86</del>	Red
14-424-1B17	14-424-1B47	14-424-1B87	Green
14-424-1B18	<del>14-424-1B48</del>	<del>14-424-1B88</del>	Yellow
14-424-1B19	14-424-1B49	14-424-1B89	Light Blue

**Solid (Tinned Copper)**

25 Feet	100 Feet	1000 Feet	Color
14-424-1L10	14-424-1L40	14-424-1L80	Gray
14-424-1L11	14-424-1L41	14-424-1L81	Black
14-424-1L12	14-424-1L42	14-424-1L82	Brown
14-424-1L13	14-424-1L43	14-424-1L83	Orange
14-424-1L14	14-424-1L44	<del>14-424-1L84</del>	Off-White
14-424-1L15	14-424-1L45	14-424-1L85	Violet
14-424-1L16	<del>14-424-1L46</del>	<del>14-424-1L86</del>	Red
14-424-1L17	14-424-1L47	<del>14-424-1L87</del>	Green
14-424-1L18	14-424-1L48	14-424-1L88	Yellow
14-424-1L19	14-424-1L49	14-424-1L89	Light Blue

### 22 AWG

**Specifications:**

Stranding: 7/30  
 Insulation Thickness: .010"  
 Insulation Material: Semi-rigid PVC  
 Nominal O.D.: .050" (Stranded), .045" (Solid)  
 Maximum Rating: 300 Volts  
 Amps Rating: 8 Amps  
 Packaging: Spool



**Stranded (Tinned Copper)**

25 Feet	100 Feet	1000 Feet	Color
14-422-1C10	14-422-1C40	<del>14-422-1C80</del>	Gray
<del>14-422-1C11</del>	<del>14-422-1C41</del>	<del>14-422-1C81</del>	Black
14-422-1C12	14-422-1C42	14-422-1C82	Brown
14-422-1C13	<del>14-422-1C43</del>	<del>14-422-1C83</del>	Orange
<del>14-422-1C14</del>	<del>14-422-1C44</del>	<del>14-422-1C84</del>	Off-White
14-422-1C15	14-422-1C45	<del>14-422-1C85</del>	Violet
<del>14-422-1C16</del>	<del>14-422-1C46</del>	<del>14-422-1C86</del>	Red
<del>14-422-1C17</del>	<del>14-422-1C47</del>	<del>14-422-1C87</del>	Green
14-422-1C18	<del>14-422-1C48</del>	<del>14-422-1C88</del>	Yellow
14-422-1C19	<del>14-422-1C49</del>	<del>14-422-1C89</del>	Light Blue

**Solid (Tinned Copper)**

25 Feet	100 Feet	1000 Feet	Color
14-422-1M10	14-422-1M40	14-422-1M80	Gray
<del>14-422-1M11</del>	<del>14-422-1M41</del>	<del>14-422-1M81</del>	Black
14-422-1M12	14-422-1M42	14-422-1M82	Brown
14-422-1M13	14-422-1M43	14-422-1M83	Orange
14-422-1M14	<del>14-422-1M44</del>	14-422-1M84	Off-White
14-422-1M15	14-422-1M45	14-422-1M85	Violet
14-422-1M16	<del>14-422-1M46</del>	<del>14-422-1M86</del>	Red
14-422-1M17	<del>14-422-1M47</del>	<del>14-422-1M87</del>	Green
14-422-1M18	14-422-1M48	14-422-1M88	Yellow
14-422-1M19	14-422-1M49	<del>14-422-1M89</del>	Light Blue