

## EPITOME® IN-WALL STEREO SPEAKERS

### Exclusive “Easy-Mount”

Mounting of our in-wall speakers is a snap with *Epitome*®’s exclusive, “Easy Mount” system. After speaker wires have been connected, just insert the speaker in the wall and tighten each of four (4) screws with a hand screwdriver. It’s that easy! The tabs rotate behind the wall, “capturing” the speaker and drawing it tight to the wall. Simple, fast and easy...and...all without the chance of dropping or losing any loose hardware.




Fig. 1

Fig. 2

Fig. 3

Fig. 4

Fig. 5

Fig. 6

### In-Wall Speakers

Retail Part No.	Fig. No.	Description	Watts Max/RMS	Frequency Response	Woofers/Magnet Wt.	Tweeter	Impedance	Weight lbs.	Dimensions			Quantity
									H	W	D	
30-4050	1	2-Way In-wall Speaker	60/30	50-20 kHz	5.25"/10 oz.	1" M SD	8 Ohms	3.31	7.5"	11"	2.75"	1 Pair
30-4060	2	2-Way In-wall Speaker	70/35	40-20 kHz	6.5"/10 oz.	1" M SD	8 Ohms	3.62	12"	8.62"	3.25"	1 Pair
30-4062	3	3-Way In-wall Speaker	100/50	40-20 kHz	6.5"/10 oz.	1" M SD	8 Ohms	3.52	12"	8.62"	3.25"	1 Pair
30-4082	3	3-Way, 2 Swivel In-wall Speaker	120/60	35-20 kHz	8.0"/20 oz.	1" M SD	8 Ohms	4.6	14.12"	10"	3.5"	1 Pair
30-4081	4	2-Way, 1 Swivel In-wall Speaker	100/50	35-20 kHz	8.0"/20 oz.	1" M SD	8 Ohms	4.19	14.5"	8.62"	3.25"	1 Pair
30-4083	5	Dual Voice Coil Sub In-wall Speaker	100/50	30-600 Hz	8.0"/26 oz.	N/A	8 Ohms	7.2	14.12"	10"	3.63"	1 Each
30-4051	6	2-Way Round In-wall Speaker	60/30	70-20 kHz	5.25"/8 oz.	.50" M SD	8 Ohms	1.98	8.0" dia. x 3.0" depth			1 Pair
30-4063	6	2-Way Round In-wall Speaker	80/40	65-20 kHz	6.5"/11 oz.	.50" M SD	8 Ohms	2.56	9.125" dia. x 3.125" D			1 Pair

\*Depth from front of wall to rear of speaker, given for clearance purpose.

## EPITOME® IN-CEILING SPEAKERS

### INTRODUCING EPITOME® MICRO SERIES®

The *Epitome*® Micro Series® are Halogen design micro-miniature speakers that blend in with Halogen Light Fixtures for Architectural Stealth Audio™. The 2-1/2" drivers are 4Ω and rated at 10 watts RMS, 20 watts Peak. Secure mounting in drywall is accomplished with two side springs. The housings are available in White and Black and are paintable so that custom colors can be applied. Perfect for background music, intercoms and paging.



Fig. 7



Fig. 8

### Epitome® Micro Series® In-Ceiling Speakers

Retail Part No.	Bulk Part No.	Figure No.	Description	Color	Watts RMS/Peak	Quantity
30-3501		7	Halogen Style Ceiling Speaker, 2.5" Diameter	Black	10/20	1 Each
30-3502		8	Halogen Style Ceiling Speaker, 2.5" Diameter	White	10/20	1 Each

For the latest information—[www.gcelectronics.com](http://www.gcelectronics.com)  
All quantities are single; BU's are packages of 10 Unless otherwise noted.