



NOTES:

1. ELECTRICAL SPECIFICATIONS
 IMPEDANCE: 75 OHMS NOMINAL
 FREQUENCY RANGE: 0-1000 MHZ
 WORKING VOLTAGE: 500 VRMS MAX
 DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS MAX
 INSULATION RESISTANCE: 500 MEGOHMS MIN
2. MECHANICAL SPECIFICATIONS
 DURABILITY: >500 CYCLES
3. ENVIRONMENTAL SPECIFICATIONS
 RECOMMENDED TEMPERATURE RANGE: -67°F TO +185 °F
 MOISTURE RESISTANCE: MEETS MIL-STD-202
4. RoHS COMPLIANT

NOTE: PLATE NI
 PLATE G $\triangle 1$

GC TM ELECTRONICS				DESCRIPTION	F-81 DUAL FEMALE CONNECTOR	SCALE	5/1	UNTTTS:MM	SRD	ANGLE
				MODEL NO	32-3999	$\triangle 1$				
APPROVED	CHECKED	DRAWING	DESIGNED	DRAWING NO		$\triangle 1$	2009/06/26		A2	
		CJJ	CJJ	FINISHING		$\triangle 1$	2005/04/13		A1	
				MATERIAL		SYE	DATE		REVISION	