



ARRANGEMENT OF CONTACTS

PARTS	
ANGLE	270°
POSITION OF VIEWS	

SPECIFICATIONS	
Dielectric strength	1,000V AC/1 Minute
Contact resistance	20m ΩMax.
Insulation resistance	100M ΩMin. at 500V DC
Rating	100V AC 2A

33-958-BU

6	PLASTIC TRAIL	1	PVC	BLACK	UL
5	PLASTIC BODY	1	NYLON [101]	BLACK	UL94V2
4	COVER-B	1	BSR-H (0.5t) [C5191]	NICKEL	3-5U"
3a	LOCKING	1	BSR-H (0.5t) [C2680R]	NICKEL	3-5U"
3	COVER-A	1	BSR-H (0.5t) [C2680R]	NICKEL	3-5U"
2	CONTACT TERMINAL	8	BSR-H (1.5D) [R-35]	SILVER PLATED	3-5U"
1	PLASTIC CORE	1	NYLON [101]	BLACK	UL94V2
P/N	PART NAME	Q'TY	MATERIAL	PLATING	REMARKS

DRAWN	KIDD	APP'D	UNIT	mm	TOLERANCE		TITLE	DIN CIRCULAR PLUG			SHEET
CHK'D			SCALE	1:1	.x ±0.20 .xx ±0.10 .xxx ±0.05 .xxxx ±0.03 ANGULA ±1°		PART NO.	DWG NO.	DIN PLUG	VERSION	A