



Model No.	Switching Position		
35-000	ON	NONE	OFF
Term. Comm.	2-3	OPEN	2-1

**SPECIFICATIONS:**

- 1.MOVABLE CONTACT: Copper alloy, silver plated
- 2.TERMINALS: Copper alloy, silver plated
- 3.RATING: 3Amps with resistive load @ 125VAC or 28VDC  
1.5Amps with resistive load @ 250VAC
- 4.CONTACT RESISTANCE: 20m-ohms max. initial
- 5.INSULATION RESISTANCE: 1,000M-ohms min.
- 6.DIELECTRIC STRENGTH: 1,000V RMS @ sea level
- 7.ELECTRICAL LIFE: 30,000 make and break cycles at full load
- 8.OPERATING TEMPERATURE: -30°C to +85°C
- 9.ROHS COMPLIANCE

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS ANGULAR TOLERANCE: ±1.0°		APPD. Amy 2009/10/01	
		CHKD. Amy 2009/10/01	
DIMENSIONS		SCALE 2 / 1	
TOLERANCE		UNIT in(mm)	
0.00 TO 10.00mm	±0.20mm	DR. Amy 2009/10/01	
10.01 TO 20.00mm	±0.25mm		
20.01 TO 30.00mm	±0.30mm		
30.01	±0.40mm	TITLE MIN TOGGLE SWITCH	
MATERIAL		SIZE A4	
		REV. 1	