



Switching Position		
ON	NONE	ON
2-3,5-6	OPEN	2-1,5-4

SPECIFICATIONS:

- 1.MOVABLE CONTACT: Copper alloy, silver plated
- 2.TERMINALS: Copper alloy, silver plated
- 3.RATING: 3Amps with resistive load @ 125VAC or 28VDC
1.5Amps with resistive load @ 250VAC
- 4.CONTACT RESISTANCE: 20m-ohms max. initial
- 5.INSULATION RESISTANCE: 1,000M-ohms min.
- 6.DIELECTRIC STRENGTH: 1,000V RMS @ sea level
- 7.ELECTRICAL LIFE: 30,000 make and break cycles at full load
- 8.OPERATING TEMPERATURE: -30°C to +85°C

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS ANGULAR TOLERANCE: $\pm 1.0^\circ$	
DIMENSIONS	TOLERANCE
0.00 TO 10.00mm	± 0.20 mm
10.01 TO 20.00mm	± 0.25 mm
20.01 TO 30.00mm	± 0.30 mm
30.01	± 0.40 mm

RoHS Compliant		GC TM ELECTRONICS	
PART NUMBER	35-002	TITLE	Toggle Switch, DPDT, On-None-On
REV. A	08/28/2012	REF. NUMBER	200-MDP-1-T1B1M1QE