



SWITCH POSITION		
ON	NONE	ON
2-3	OPEN	2-1

SPECIFICATIONS:

- 1.MOVABLE CONTACT: Copper alloy, silver plated
- 2.TERMINALS: Copper alloy, silver plated
- 3.RATING: 5Amps with resistive load @ 120VAC or 28VDC
2Amps with resistive load @ 250VAC
- 4.CONTACT RESISTANCE: 10m-ohms max. initial
- 5.INSULATION RESISTANCE: 1,000M-ohms min.
- 6.DIELECTRIC STRENGTH: 1,000V RMS @ sea level
- 7.ELECTRICAL LIFE: 50,000 make and break cycles at full load
- 8.OPERATING TEMPERATURE: -30°C to +85°C

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS ANGULAR TOLERANCE: ±1.0°	
DIMENSIONS	TOLERANCE
0.00 TO 10.00mm	±0.20mm
10.01 TO 20.00mm	±0.25mm
20.01 TO 30.00mm	±0.30mm
30.01	±0.40mm

RoHS Compliant		GC TM ELECTRONICS
PART NUMBER	35-004	TITLE
REV. A	08/28/2012	REF. NUMBER
		Toggle Switch, SPDT, On-None-On 100-SP-1-T100B1M1QE