


PANEL CUTOUT



PANEL THICKNESS: (0.029 - 0.098)

SPECIFICATIONS		RU & E RECOGNIZED
POLES / THROWS:	SPDT	
CURRENT RATING:	16A, 1 HP - 250Vac; 1/2 HP - 125Vac; 16A - 250Vac NON IND; T125 16(4) - 250Vac	
INITIAL CONTACT RESISTANCE:	5 MILLI-OHMS MAX.	
INSULATION RESISTANCE:	100 MEGA-OHMS MIN.	
DIELECTRIC STRENGTH:	1,500Vac MIN.	
CONTACT MATERIAL:	SILVER	
TERMINAL MATERIAL:	BRASS - SILVER PALTED	
TERMINAL TYPE:	COMBINATION SOLDER & .250 QUICK CONNECT	

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWINGS ARE THE PROPERTY OF GC ELECTRONICS. REPRODUCTION OR DISTRIBUTION OF THIS DRAWING MUST HAVE PRIOR WRITTEN CONSENT FROM GC ELECTRONICS.

SHEET 1 OF 1 SCALE NTS :      DIMENSIONS INCHES

TOLERANCE	NO.	CHANGE	DATE

# GC Electronic

PART NAME: **ROCKER SW, SPDT, ON/ON**

MATL:

DRAWN: **S.R.S.** / 6/22/04 / PART NO. **35 - 640**

CHECKED:  / REV: